



Renovar® 4T ECO SYNTHETIC BLEND (API SN)

(Premium Quality, Multigrade, High Performance Engine Oils)

Renovar® 4T is an ideal premium mineral lubricant for standard or mid-sized engine motorcycles. These mid-size engines require reliable engine oil performance under a range of conditions during stop-start commuter journeys.

PERFORMANCE BENEFITS PREMIUM FORMULATION

- Made using technology from USA, blended using the best of severely hydrocracked mineral base stocks and premium top-tier synthetic additives available today

OIL PERFORMANCE RELIABILITY

- Special oil formulation to keep oil viscosity in grade longer. Enhanced wear protection actions against valve train wear. Enhanced cleanliness. Removal of sludge and engine deposits.

ADVANCED CONTROL

- Smooth Clutch and superior gearbox operation, optimized viscometrics for smoother clutch engagement & gear changes.

APPLICATIONS

- Mid-Sized and water-cooled four stroke motorcycle engines. Offers enhanced performance for underbones and mopeds.

MEETS SPECIFICATIONS & APPROVALS:

- API SN
- JASO MA

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

RENOVAR® API SN ECO SYN					
SAE Viscosity Grade	15W40	20W40	20W50	10W30	SAE40
Kinematic viscosity at 40°C (cSt)	106.4	124	172	75.5	139
Kinematic viscosity at 100°C (cSt)	14.5	14.3	19.5	11.5	14.4
Density at 15°C	0.878	0.885	0.885	0.868	0.9
Flash point, °C	215	240	235	212	250
Pour point, °C	-30	-24	-24	-33	-9
Viscosity Index	155	114	130	145	102

These characteristics are typical of current production. Whilst future production will conform to RENOVAR®'s specification, variations in these characteristics may occur.