



Renovar® 4T PREMIUM SEMI SYNTHETIC (API SN)

(Premium Quality, Multigrade, High Performance Engine Oils)

Developed using technology from USA, a premium blend using high end synthetic and mineral base stocks together with the best top-tier additives available today. Renovar® 4T has developed a superior semi-synthetic lubricant that gives optimal protective performance that keeps your vehicle running like new day after day.

PERFORMANCE BENEFITS PREMIUM FORMULATION

- Developed using technology from the USA, blended using the best of fully synthetic base stocks and the latest in premium additives.

OIL PERFORMANCE RELIABILITY

- Special oil formulation to keep oil viscosity in grade longer. Enhanced wear protection actions against valve train wear. Enhanced cleanliness. Removal of sludge and engine deposits.

ADVANCED CONTROL

- Smooth Clutch and superior gearbox operation, optimized viscometrics for smoother clutch engagement & gear changes.

APPLICATIONS

- Mid-Sized and water-cooled four stroke motorcycle engines. Offers enhanced performance for underbones and mopeds.

MEETS SPECIFICATIONS & APPROVALS:

- API SN/SM/SL
- JASO MA
- JASO MA2

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

RENOVAR® 4T API SN SEMI SYNTHETIC

SAE Viscosity Grade	10W30	10W40	15W50
Kinematic viscosity at 40°C (cSt)	72.66	97.53	142.1
Kinematic viscosity at 100°C (cSt)	11	15	18.8
Density at 15°C	0.87	0.871	0.886
Flash point, °C	219	220	228
Pour point, °C	-33	-33	-30
Viscosity Index	145	155	145

These characteristics are typical of current production. Whilst future production will conform to RENOVAR®'s specification, variations in these characteristics may occur.