



Renovar®

AUTOMATIC TRANSMISSION FLUID DEXRON IIIH

(High Performance Automatic Transmission Fluid)

Renovar® Automatic Transmission Fluid is a premium quality automatic transmission fluid based on superior quality base oils and carefully selected additives. It is blended to meet the stringent requirements of leading automotive transmission manufacturers.

PERFORMANCE BENEFITS

- Provides reliable, smooth, trouble free and consistent all weather shifting of automotive transmission systems.
- Resistant to oil degradation and keeps automatic transmissions clean.
- Excellent oil fluidity at low temperatures.
- Appropriate friction performance
- High shear stability
- Increased anti-wear and oxidation stability for longer component life and a longer service interval.

APPLICATIONS

- Passenger car automatic transmissions.
- Heavy duty automatic transmissions.

MEETS SPECIFICATIONS & APPROVALS:

- GENERAL MOTORS DEXRON III
- FORD MERCON
- ALLISON C-4

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

RENOVAR® AUTOMATIC TRANSMISSION FLUID DEXRON IIIH

SAE Viscosity Grade	-
Kinematic viscosity at 40°C (cSt)	33.8
Kinematic viscosity at 100°C (cSt)	7.2
Density at 15°C	0.8432
Flash point, °C	240
Pour point, °C	-48
Viscosity Index	160

These characteristics are typical of current production. Whilst future production will conform to RENOVAR®'s specification, variations in these characteristics may occur.