



Renovar® SYNTHETIC PREMIUM INDUSTRIAL GEAR OILS

(High Quality Industrial Gear and Bearing Oils)

Renovar® Industrial Gear Oils are multi purpose gear oils that meet or exceed all key industry standards.

PERFORMANCE BENEFITS

PREMIUM FORMULATION

- Outstanding oxidation and thermal stability which helps extend oil life.
- Effective corrosion inhibition to help protect gearbox components.
- Wide range of viscosities to meet a wide variety of operating conditions.
- Excellent load carrying capacity helping to extend equipment life

APPLICATIONS

- Industrial gear drivers where extreme pressure performance due to heavy or shock loading is needed.
- Plain and roller contact bearings.
- Circulating and splash lubricated systems.

PACKGING

- 1L , 4L , 5L ,6L 7L , 18L , 20L , 200L, 209L, 1000L

MEETS SPECIFICATIONS & APPROVALS:

- ISO 12925-1 CKC-D
- AGMA 9005-E02
- AGMA 251.02-04
- US Steel 224
- ALSO meets Brown Types M,A and E

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

RENOVAR® INDUSTRIAL SYNTHETIC BLEND GEAR OIL

SAE Viscosity Grade	220	320	460
Kinematic viscosity at 40°C (cSt)	220	320	460
Kinematic viscosity at 100°C (cSt)	30	37	53
Density at 15°C	864	866	868
Flash point, °C	240	240	240
Pour point, °C	-42	-42	-42
Viscosity Index	171	169	179
Four Ball EP Weld load	250	250	250

These characteristics are typical of current production. Whilst future production will conform to RENOVAR®'s specification, variations in these characteristics may occur.